

FISHING LINE AND LURE CONNECTORS

Invented by

Michael L. Denby

a resident of

6643 East Aster Drive  
Scottsdale, Arizona 85254

a citizen of  
the United States

094650-04100

# FISHING LINE AND LURE CONNECTORS

## Field of the Invention

This invention relates to angling accessories and, more particularly, to connectors for securing lines and lures.

## Background of the Invention

A fisherman is no better than his knots. It is no good to own the best tackle and have an abundance of fishing knowledge and skill if, when fish are hooked, knots give way. The angler must therefore pay close attention to his knots. Under most conditions, an angler needs to know how to tie only a few knots, which, for most fishermen, include the clinch knot for fastening lures to leaders and tippets, the blood knot for fastening tippets to leaders and the nail knot for fastening leaders to fly lines. On a windy day, a cold day when hands are cold and for the elderly fisherman who has lost dexterity in his hands, tying knots can prove difficult and frustrating. Although the well-traveled angler typically employs a vast arsenal

1 of gadgets and accessories in practicing his art, needed is  
2 yet another to provide the angler with a way to easily  
3 fasten lures to leaders and tippets, tippets to leaders and  
4 leaders to fly lines.

5

6 Accordingly, it would be highly desirable to provide  
7 new and improved connectors for securing lines and lures.

8

9 It is another purpose of the invention to provide new  
10 and improved connectors that are easy to use.

11

12 It is still another purpose of the invention to  
13 provide new and improved connectors that are easy and  
14 inexpensive to construct.

15

16 It is a further provision of the invention to  
17 eliminate the need and difficulty of tying attachment  
18 knots.

19

20 It is still a further purpose of the invention to  
21 provide new and improved connectors that are strong, easy  
22 to install and transport, and highly efficient.

1           It is yet still a further purpose of the invention to  
2   increase the ease and efficiency of exchanging lures during  
3   fishing activity.

007740" 20594560

Summary of the Invention

The above problems and others are at least partially solved and the above purposes and others realized in new and improved connectors for securing lines and lures. In one embodiment, provided is a connector for receiving and securing an end segment of a line. The end segment defines an outer diameter. The connector is comprised of a receptacle including a chamber bound by a substantially continuous sidewall defining an inner diameter that is substantially equal to the outer diameter of the end segment of the line. The connector supports extensions or teeth which extend into the chamber for impinging against the end segment. The receptacle is resilient and deformable, and the extensions are positioned at spaced intervals along substantially the entire length of the chamber. The extensions are directed away from an open end of the receptacle which leads to the chamber for providing a maximum engagement. The receptacle supports a coupler or line, which are each capable of engaging and supporting a lure. In accordance with another embodiment of the invention, receptacle may be supported by or formed at or into at least one of the opposing ends of a length of line, such as the butt end of a leader.



0954502 "04.1.00

1 chamber at spaced intervals along substantially the entire  
2 length of the first chamber, and are directed away from an  
3 opening leading to the first chamber. The second chamber  
4 also includes a length, and the second extensions extend  
5 into the second chamber at spaced intervals along  
6 substantially the entire length of the second chamber, and  
7 are directed away from an opening leading to the second  
8 chamber.

9

10 In accordance with yet another embodiment, provided is  
11 a connector for receiving and securing an end segment of a  
12 line. The end segment includes an outer diameter and the  
13 connector is comprised of a receptacle including a chamber  
14 bound by a substantially continuous sidewall defining an  
15 inner diameter. The connector is resilient and deformable  
16 between shortened and lengthened conditions. The connector  
17 is constructed and arranged such that the inner diameter is  
18 maximized in the shortened condition and minimized in the  
19 lengthened condition. The receptacle supports a biasing  
20 element or framework which biases the receptacle into the  
21 lengthened condition. The biasing element also which  
22 facilitates the minimum and maximum inner diameters of the  
23 receptacle when the connector is moved into and between the  
24 shortened and lengthened conditions. The inner diameter of





1 receiving and securing one of the first and second end  
2 segments and an opposing receptacle for receiving and  
3 securing the other of the first and second end segments.  
4 The first receptacle includes a first chamber bound by a  
5 substantially continuous sidewall which defines an inner  
6 diameter. The first receptacle is resilient and deformable  
7 between shortened and lengthened conditions. The body is  
8 constructed and arranged such that the inner diameter is  
9 maximized in the shortened condition and minimized in the  
10 lengthened condition. The first receptacle supports a  
11 first biasing element or framework for biasing the first  
12 receptacle into the lengthened condition. The first  
13 biasing element also facilitates the minimum and maximum  
14 inner diameters of the first receptacle when the first  
15 receptacle is moved into and between the shortened and  
16 lengthened conditions. The inner diameter of the first  
17 receptacle in the shortened condition is greater than the  
18 outer diameter of the one of the first and second end  
19 segments, and the inner diameter of the first receptacle in  
20 the lengthened condition is less than or at least  
21 substantially equal to the outer diameter of the one of the  
22 first and second end segments. The second receptacle  
23 includes a second chamber bound by a substantially  
24 continuous sidewall defining an inner diameter that is

0254502.041100

1 substantially equal to the outer diameter of the other of  
2 the first and second end segments. The second receptacle  
3 deformable between shortened and lengthened conditions.  
4 The body is constructed and arranged such that the inner  
5 diameter of the second receptacle is maximized in the  
6 shortened condition and minimized in the lengthened  
7 condition. The second receptacle supports a second biasing  
8 element or framework for biasing the second receptacle into  
9 the lengthened condition. The second biasing element also  
10 facilitates the minimum and maximum inner diameters of the  
11 second receptacle when the second receptacle is moved into  
12 and between the shortened and lengthened conditions. The  
13 inner diameter of the second receptacle in the shortened  
14 condition is greater than the outer diameter of the other  
15 of the first and second end segments, and the inner  
16 diameter of the second receptacle in the lengthened  
17 condition is less than or at least substantially equal to  
18 the outer diameter of the other of the first and second end  
19 segments.

20  
21 The first and second biasing elements are preferably  
22 integrally formed with the first and second receptacles,  
23 respectively. The first receptacle may be equipped with  
24 first extensions or teeth extending into the first chamber

1 for impinging against the one of the first and second end  
2 segments. If provided, the first extensions or teeth  
3 preferably extend into the first chamber at spaced  
4 intervals along substantially the entire length of the  
5 first chamber and away from an opening leading to the first  
6 chamber. The second receptacle may be equipped with second  
7 extensions or teeth extending into the second chamber for  
8 impinging against the other of the first and second end  
9 segments. If provided, the second extensions or teeth  
10 preferably extend into the second chamber at spaced  
11 intervals along substantially the entire length of the  
12 second chamber and away from an opening leading to the  
13 second chamber.

09546502 "04.1.100

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and further and more specific objects and advantages of the invention will become readily apparent to those skilled in the art from the following detailed description taken in conjunction with the drawings in which:

Fig. 1 illustrates a connector coupling a lure to a line, the connector being shown as it would appear in use by an angler;

Fig. 2 is an enlarged perspective view of the connector of Fig. 1;

Fig. 3 is a sectional view taken along line 3-3 of Fig. 2;

Fig. 3A is a view very similar to the view of Fig. 3, with the connector shown as it would appear securing a line;

Fig. 4 is a front view of the connector of Fig. 2;

1        Fig. 5 is a perspective view of another embodiment of  
2 a connector for coupling a lure to a line;

3

4        Fig. 5A is a sectional view taken along line 5A-5A of  
5 Fig. 5;

6

7        Fig. 6 is a front view of the connector of Fig. 5;

8

9        Fig. 7 is a perspective view of yet another embodiment  
10 of a connector for coupling a lure to a line;

11

12        Fig. 8 is a sectional view taken along line 8-8 of  
13 Fig. 7;

14

15        Fig. 9 is a perspective view of a length of line  
16 constructed in accordance with the invention;

17

18        Fig. 10 is a sectional view taken along line 10-10 of  
19 Fig. 9;

20

21        Fig. 11 is a perspective view of a connector for  
22 securing two lines;

1        Fig. 12 is a sectional view taken along line 12-12 of  
2   Fig. 11;

3

4        Fig. 12A is a view very similar to the view of Fig.  
5   12, with the connector shown as it would appear securing  
6   two lines;

7

8        Fig. 13 is a perspective view of yet still another  
9   embodiment of a connector for connecting a lure to a line;

10

11       Fig. 14 is a sectional view taken along line 14-14 of  
12   Fig. 13;

13

14       Fig. 15 is a view very similar to the view of Fig. 14,  
15   with the connector as it would appear receiving a line; and

16

17       Fig. 16 is a view very similar to the view of Fig. 15,  
18   with the connector shown as it would appear securing a  
19   line.

1 DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

2

3 Turning to the drawings, in which like reference

4 characters indicate corresponding elements throughout the

5 several views, attention is first directed to Fig. 1, which

6 illustrates a connector 20 for coupling a lure 21 to a line

7 22 (shown in phantom line). Connector 20 is shown in Fig.

8 1 being employed by an angler 23 shown in phantom outline.

9 Regarding Fig. 2, connector 20 is constructed of or formed

10 from nylon or other similarly resilient, strong and

11 deformable material, and is comprised of a receptacle 25

12 and a coupler 26. Turning to Fig. 3, receptacle 25 is

13 elongate and includes a continuous sidewall 30 having

14 opposing ends 31 and 32. End 32 is open and leads to a

15 chamber 33 bound by sidewall 30. End 31 is preferably

16 closed, but it may be open if so desired so as to

17 communicate with chamber 33. Chamber 33 is elongate and

18 defined by a continuous inner surface 34 of sidewall 30.

19 Surface 34 defines an inner diameter D of chamber 33 that

20 is substantially constant along substantially the entire

21 length of chamber 33 from end 32 to end 31. Protrusions,

22 extensions or teeth 35 extend into chamber 33 from inner

23 surface 34 and are positioned at spaced intervals along

24 substantially the entire length of chamber 33 from end 32

1 to end 31. Teeth 35 are flexible and resilient, preferably  
2 molded, formed or integral with sidewall 30, and face away  
3 from end 32.

4

*Dep. 21*  
5 Regarding Fig. 3A, receptacle 25 is designed to  
6 receive and secure an end segment 41A of a line 41. In  
7 this example, line 41 is a fishing line such as a tippet or  
8 leader formed of nylon monofilament, and end segment 41A is  
9 a length of line 41 leading to its free end 41B. Inner  
10 diameter D of chamber 33 is substantially equal to the  
11 outer diameter of end segment 41A. To install connector  
12 20, connector 20 is held and end 41B forced into chamber 33  
13 through end 32. Because teeth 35 are slanted or directed  
14 away from open end 32, flexible and resilient, chamber 33  
15 readily accepts end segment 41A without considerable effort  
16 or difficulty. When installed in chamber 33, it is  
17 preferred that free end 41B reside against or immediately  
18 adjacent end 31 of receptacle 25.

19

20 Because inner diameter D of chamber is substantially  
21 constant from end 32 to end 31 of receptacle 25 and  
22 substantially equal to the outer diameter of end segment  
23 41B, the fit of end segment 41A against inner surface 34 of  
24 chamber 33 is tight, snug or close. This forces teeth 35



1 to impinge against end segment 41A. In Fig. 3A, an  
2 exaggerated space is shown between end segment 41A and  
3 inner surface 34 of chamber 33 for ease of illustration.  
4 The slanted orientation of teeth 35 away from end 32, the  
5 snug fit of end segment 41A in chamber 33 and the  
6 impingement of teeth 35 against end segment 41A cooperate  
7 to grippingly seize or secure end segment 41A in place, and  
8 inhibits end segment 41A from dislodging from chamber 33  
9 through open end 32 while under a pulling force. Although  
10 teeth 35 are flexible and resilient, the snug fit between  
11 inner surface 34 and end segment 41A prevents teeth 35 from  
12 buckling under force and compels them to impinge against  
13 end segment 41A, which provides a surprisingly strong and  
14 highly effective coupling.

15  
16 Most fisherman use fishing lines with outer diameters  
17 that range from 0.004 to 0.021 of an inch. Smaller and  
18 larger sizes can, however, be found. Depending on the  
19 needs of the angler and the fishing line he is using,  
20 receptacle 25 is preferably from 0.5-8.0 cm in length and  
21 1-10 mm in outer diameter, with the thickness of sidewall  
22 30 falling from 0.5-4.0 mm. However, receptacle 25 may  
23 incorporate any suitable or desired dimensions consistent  
24 with the teachings of this disclosure.

1 With regard to Figs. 2 and 3, coupler 26 is supported  
2 by and extends away from end 31 of receptacle 25, and is  
3 designed to engage the hook eye of a lure, obviating the  
4 need to tie a clinch knot, a Turle knot, a Homer Rhode loop  
5 knot, end-loop knot or other suitable lure-to-line  
6 connection knot. In this embodiment, coupler 26 is  
7 comprised of a pair of resilient hooks 40 and 41, which  
8 extend away from end 31 and engage one another in an  
9 overlapping state (see Fig. 4) forming a continuous loop.  
10 Hooks 40 and 41 are substantially coextensive, biased  
11 together, and may made of the same material as receptacle  
12 25 or a different material. A lure is engagable to coupler  
13 26 by forcing hooks 40 and 41 apart and threading the free  
14 end of one of the hooks 40 and 41 into and through the hook  
15 eye of the lure. The engagement of hooks 40 and 41 in the  
16 overlapping state prevents the attached lure from falling  
17 off. Hooks 40 and 41 are constructed of a size that will  
18 permit the overlapping portions to readily pass through the  
19 hook eye of the lure. To remove the lure, the foregoing  
20 operation need only be reversed.

21

22 The coupler of the invention may be provided in many  
23 forms suitable for permitting engagement to the hook eye of  
24 a lure. As a matter of example Figs. 5, 5A and 6

1 illustrate another embodiment of a connector 45, which is  
2 comprised of a receptacle 46 and another embodiment of a  
3 coupler 47. Receptacle 46 incorporates the same structural  
4 features as receptacle 25. Accordingly, details of  
5 receptacle 46 will not be discussed. Coupler 47 is  
6 comprised of a pair of resilient plates 48 and 49, which  
7 extend away from the closed end of receptacle 46 in an  
8 overlapping state. Plates 48 and 49 are substantially  
9 coextensive, biased together and made of the same material  
10 as receptacle 46. Plate 48 carries a prong 50, which  
11 resides between a pair of prongs 51A and 51B carried by  
12 plate 49. Prongs 50, 51A and 51B cooperate together to  
13 hold or clutch the hook eye of a lure when it is slipped  
14 between plates 48 and 49. To facilitate easy insertion of  
15 the hook eye between plates 48 and 49, prongs 50, 51A and  
16 51B are outwardly beveled. To remove the lure, a user need  
17 only grasp lure, twist it to forcefully separate plates 48  
18 and 49 and then move the lure away.

19  
20 Turning now to Figs. 7 and 8, shown is a connector 54  
21 constructed in accordance with yet another embodiment of  
22 the invention. Connector 54 is comprised of a receptacle  
23 55 and a line 56. Receptacle 54 incorporates the same  
24 structural features as receptacle 25 discussed previously.

1 Accordingly, details of receptacle 54 will not be  
2 discussed. Line 56 is formed with and extends from end 57  
3 of receptacle 54. In this embodiment, end 57 is closed.  
4 It is intended that line 57 comprise tippet of a specified  
5 length and having a free end available for tying to a lure  
6 in a conventional manner. In this embodiment, receptacle  
7 54 is designed to engage the end of a leader, obviating the  
8 need to tie a blood knot or other suitable line-to-line  
9 connection knot.

10  
11 Regarding Figs. 9 and 10, shown is a length of line 60  
12 constructed in accordance with the invention. Line 60 is  
13 elongate, includes opposing ends 61 and 62, and is  
14 constructed or formed of a resilient, strong and deformable  
15 material such as nylon or other suitable material. In this  
16 embodiment, line 60 is shown in the form of a tapered  
17 leader, with end 61 comprising the butt end and end 62  
18 comprising the tail end. Line 60 can comprise a level  
19 leader if so desired. Formed into end end 61 is a  
20 receptacle 63, which incorporates the same structural  
21 features as receptacle 25. Accordingly, details of  
22 receptacle 63 will not be discussed. In this embodiment,  
23 line 60 is designed to function as the nearly invisible  
24 connection between a lure and, for instance, a fly line or

1 other form of fishing line. Receptacle 63 secures an end  
2 segment of the fly line, which obviates the need to tie a  
3 nail knot or other suitable leader-to-fly line connection  
4 knot.

5

6 Attention is now directed to Figs. 11, 12 and 12A,  
7 which illustrate a connector 70 for securing two lines such  
8 as a fly line and a leader or a leader and tippet, and for  
9 securing together monofilament of different diameters. In  
10 this embodiment, connector 70 is comprised of an elongate  
11 body or sleeve 71 having opposing receptacles 72 and 73 on  
12 either side of sleeve 71. Receptacles 72 and 73 each  
13 incorporate the same structural features as receptacle 25.  
14 Accordingly, details of receptacles 72 and 73 will not be  
15 discussed. However, in this embodiment the closed ends of  
16 receptacles 72 and 73 face one another and the open ends of  
17 receptacles 72 and 73 face away from one another. The axes  
18 defined by receptacles 72 and 73 are substantially common  
19 as clearly shown in Figs. 12 and 12A. Figure 12 shows two  
20 lines 74 and 75 each shown as they would appear secured to  
21 receptacles 72 and 73, respectively. The diameters of  
22 receptacles 72 and 73 may be substantially the same for  
23 facilitating a coupling between lines having substantially  
24 identical diameters, or different for facilitating a

1 coupling between lines having different diameters. Body 71  
2 is preferably molded or otherwise integrally formed of a  
3 resilient, strong and deformable material such as nylon or  
4 other suitable material, and obviates the need for an  
5 angler to tie a blood knot, surgeon's knot, shocker knot or  
6 other suitable line-to-line connection knot.

7

8 Turning now to Figs. 13-16, illustrated is still  
9 another embodiment of a connector 80 for connecting a lure

10 to a line. Connector 80 is constructed of or formed from  
11 nylon or other similarly resilient, strong and deformable  
12 material, and is comprised of a receptacle 81 and a coupler  
13 82. As best shown in Fig. 14, receptacle 81 is elongate  
14 and includes a continuous sidewall 83 having opposing ends  
15 84 and 85. End 85 is open and leads to a chamber 86 bound  
16 by sidewall 83. End 84 is preferably closed, but it may be  
17 open if so desired. Chamber 86 is elongate and defined by  
18 a continuous inner surface 87 of sidewall 83. Surface 87  
19 defines an inner diameter  $D'$  of chamber 86 that is  
20 substantially constant along substantially the entire  
21 length of chamber 86 from end 85 to end 84. Although not  
22 shown, protrusions, extensions or teeth may be provided to  
23 extend into chamber 86 from inner surface 87 at spaced  
24 intervals along substantially the entire length of the

1 chamber 86 from end 85 to end 84. If provided, these teeth  
2 35 are preferably flexible and resilient, molded, formed or  
3 integral with sidewall 83, and face away from end 85.  
4 Coupler 82 may comprise the structure of coupler 26  
5 discussed previously in connection with connector 20 or  
6 coupler 47 discussed previously in connection with  
7 connector 45. In lieu of coupler 82, a line may be used,  
8 much like line 56 discussed previously in connection with  
9 coupler 54.

10  
11 Receptacle 81 is deformable between a shortened  
12 condition shown in Fig. 15 and a lengthened condition shown  
13 in Figs. 13, 14 and 15. Receptacle 81 supports or is  
14 otherwise equipped with a biasing element or framework 92,  
15 which is constructed and arranged for biasing receptacle 81  
16 into the lengthened condition and for resisting the  
17 movement of receptacle 81 into the shortened condition.  
18 Biasing element 92 may comprise a discrete device that  
19 fastened or otherwise coupled to receptacle 81 or, in  
20 regards to a preferred embodiment, formed or molded  
21 integral with receptacle 81 as substantially shown. In  
22 this embodiment, biasing element 92 is comprised of a  
23 spring 93, which has the form of a coiled element or  
24 framework much like a conventional compression spring.

09546502-04100  
DOT-T-40-2059450

1 However, biasing element 92 may comprise ribbing or other  
2 framework construction suitable for biasing receptacle 81  
3 into the lengthened condition. Due to the resiliency and  
4 deformability of receptacle 81, spring 93 is constructed  
5 and arranged in such a way that it causes inner diameter D'  
6 of receptacle 81 to increase or maximize in the shortened  
7 condition of receptacle 81 and decrease or minimize in the  
8 lengthened condition of receptacle 81. Consistent with  
9 this disclosure, biasing element 92 may be provided as a  
10 framework of any appropriate structure capable of carrying  
11 the same function as spring 93.

12  
13 Receptacle 81 is designed to receive and secure an end  
14 segment 90A of a line 90. In this example, line 90 is a  
15 fishing line such as a tippet or leader formed of nylon  
16 monofilament, and end segment 90A is a length of line 90  
17 leading to its free end 90B. When receptacle 81 is in the  
18 lengthened condition, inner diameter D' of chamber 86 is  
19 less than or at least substantially equal to the outer  
20 diameter of end segment 90A. When receptacle 81 is in the  
21 shortened condition, inner diameter D' of chamber 86 is  
22 greater than the outer diameter of end segment 90A.



1 To install connector 80, connector 80 is held and end  
2 90B forced into chamber 86 from end 85. The bias of spring  
3 93 may be overcome in response to a sufficient force  
4 exerted in the act of forcing end 90B of line 90 into and  
5 through end 85. This causes receptacle 81 to move into the  
6 shortened condition, which increases inner diameter D' and  
7 allows end 90B to pass into chamber 86 through end 85 as  
8 shown substantially in Fig. 15. When end segment 90A is  
9 properly inserted into chamber 86, spring 93 biases  
10 receptacle 81 into the extended condition as shown  
11 substantially in Fig. 16, which causes inner diameter D' to  
12 decrease or otherwise move into or near its minimized  
13 condition which causes inner surface 87 to frictionally  
14 grip, seize or clutch end segment 90A. This frictional  
15 seizing of end segment 90A is sufficient to provide a  
16 strong, efficient coupling between receptacle 81 and line  
17 90, which inhibits end segment 90A from dislodging from  
18 chamber 86 through end 85 while under a pulling force.  
19 When end segment 91A is installed into chamber 86 in this  
20 manner, it is preferred that end 90B reside against or  
21 immediately adjacent end 84 of receptacle 81. To enhance  
22 the coupling between receptacle and end segment 90A, inner  
23 surface 87 be textured as generally shown in Fig. 14 or  
24 provided with teeth as discussed above.

1 In view of this disclosure, the skilled artisan will  
2 readily appreciate that receptacle 81 may be formed at or  
3 into the butt end of a leader much like leader 60  
4 previously discussed in combination with Figs. 9 and 10,  
5 and that two receptacles 81 may be formed into a connector  
6 for connecting two lines together like connector 70  
7 previously discussed in combination with Figs. 11, 12, and  
8 12A. Also, each connector discussed in this specification  
9 may be rated or otherwise constructed to withstand the same  
10 pressure or pounds as a corresponding fishing line so as to  
11 give only when the corresponding fishing line itself would  
12 have given. When a coupler or an attached line breaks, the  
13 angler need only clip the line to form a clean free end and  
14 then attach a desired coupler consistent with the teachings  
15 of this disclosure.

16  
17 The invention has been described above with reference  
18 to one or more preferred embodiments. However, those  
19 skilled in the art will recognize that changes and  
20 modifications may be made in the described embodiments  
21 without departing from the nature and scope of the  
22 invention. Various changes and modifications to one or  
23 more of the embodiments herein chosen for purposes of  
24 illustration will readily occur to those skilled in the

1 art. To the extent that such modifications and variations  
2 do not depart from the spirit of the invention, they are  
3 intended to be included within the scope thereof, which is  
4 assessed only by a fair interpretation of the following  
5 claims.

6

7 Having fully described the invention in such clear and  
8 concise terms as to enable those skilled in the art to  
9 understand and practice the same, the invention claimed is:

0954502-04-1100